

Orange Juicer

USER MANUAL

USER'S MANUAL



Orange Juicer

TT-J113



1. Brief

The Juicer's squeeze system is made of aluminum alloy and was created by advanced technology. The internal conformation is compact and reasonable. They are all made of stainless steel where get in touch with food. The advantage of this product is that it can resist decay, not easy to be rusted and easy to be cleaned. Turning on this machine for several seconds you can get the fresh tasty and delicious syrup. At present it is a satisfied machine for the hotel, restaurant and shops. All kinds of fresh melon fruit and vegetable can be squeezed, such as watermelon, cantaloupe, apple, pear, orange, peach, almond, pineapple, grape, carrot, celery and etc. The residue will be separated voluntarily from the syrup. The handle of residue is convenience. The rate of juice gets to 75%. Because the operation is convenience and easy, as soon you use the juicer as you can get the fresh and original syrup and you can choose the fruit and vegetable freely. The syrup is healthy nature and secure. It is the necessary way for the drink's renewing.

2. Parameters

VOLTAGE	220V-240V 50/60Hz
POWER	180W
Weight	7KG
Rotating speed	4300 RPM

3. Prepare before operating

- A. Power supply of 220-240V, the power supply must have the safety system to connect with the ground. Please don't replace the machine's cable by user.
- B. Check the lid whether lock closely with the bower centering (You can pull the spigot of juice for cask that made of stainless steel if not move) If it is lax you can re-adjust the lock pin.
- C. Connect the power supply and turn on the machine, examine the machine with your eyes and ears to make sure the function normally before work.

4. Operation

Please clean the fruit or vegetable you want to squeeze and peel off the skin, such as orange and watermelon. Some fruit like peach and apricot they have the firm pip so you have to take out them or it will shatter machine. Cutting the pulp into piece or cube which smaller that the size of the ostium for putting the pulp. Then put them into clean container. When turn on the machine you can put the pulp into ostium continuously or use the fruit pusher, then the fresh juice will pour from the ostium. If you want to change fruit or vegetable when the machine working in normally, infusing clean water into ostium it will be cleaned and the peculiar smell will be resisted.

5. After operation

If you want to clean or change the blade and centrifugation basket after you use the machine over. You must turn off the power then you can open the lid and screw off the nut, take out the blade, centrifugation basket to clean completely (Don't move the other parts avoid to effect the quality for boot-strap). Finally install the parts with reversed sequence. Putting on the lid then the machine can work normally again.