

Commercial Orange Juicer

User Manual

USER MANUAL
MODEL TT-J24

The juicer made of aluminum and was created by advanced craft. The internal construction is tightly packed and reasonable. there are all made of stainless steel where get in touch with food. The advantage of this production : resist decay not easy trust ,easy to cleaning .Turn on this machine after some time you can get the syrup that is fresh, tasty, delicious .It's a very good machine of manufacture for hotel ,restaurant and grocery.

All kinds of fresh melon, fruit and vegetable can be squeezed .For example :watermelon, cantaloupe, apple, pear, orange, pomelo, peach, almond, pineapple, grape, carrot, celery and so on. It's easy and convenience to operation for whole process because the volume is small. Not only get the juice quickly but also the juice and dregs separate. The dregs vent automatic and it's convenience to handle .The rate of juice amount to 75%.You can drink as soon as fruit be squeezed and the juice is nature and necessary way to refresh drink.

Please attention the operation before you use this machine.

1 The data of main technology.

Model:TT-J25	Voltage:220v-240v	Power:370w
Weight:12kg	Frequency:50-60Hz	Rev:2800r/min

2 Attention to be paid before operation.

A Electricity of 220v-240v. The power supply must have the safety system to connect the ground. Please don't replace the machine's cable by yourself.

B Check the upper cover weather lock with the shelf.(You can pull the spigot of juice for cask that made of stainless steel ,if it not move, it's correct ,or ,you must open the upper cover repeat and adjust the hook, then lock the upper cover with shelf, make the cask con not move.)

C Connect to the power supply and turn on the machine, examine the machine with your eyes and ears to make sure the function normally before normal work

3 The process of operation.

Please clean the goods before squeeze and peel off if it need.(For example :orange , pomelo, water melon).Some fruit like peach and apricot are hardness so you must remove the stone otherwise it will shatter machine. Cutting the pulp to piece smaller than the size of the ostium. then put it in clean case .While turn on the machine you can put the pulp into ostium continuons or use the stick of push ,then the fresh juice will pour from the ostium. If you want to change the goods of juice and the machine worked in normally , after clean water into ostium ,it will be cleaned and the peculiar smell will be resist.

4 After operation

If you want to clean or change the blade and filter after you use the machine over. You must turn off the power then you can open the upper cover and screw a lid off the nut ,take out the blade, filter, cask to clean completely(Don't move the other parts to tamper with the quantity for boot-strap).Finally install the parts accord with reversed sequence. Put on the upper cover to repeat.